



Please Approve this Drawing	
Date	
Signature	

NO.	Part Nome	Q'TY	Material	Plated surface
1	Plunger	1	HBi59	Au 10u" Min. OVER 50~120 U" NI
2	Barrel	1	HBi59	Au 5u" Min. OVER 50~120 U" NI
3	Spring	1	SUS 304	Au 1u" Min.
4	CAP	1	High temp.Plastic; UL94 V-0 Color Black	



NOTES:

- Electrical
 - .Rated Current & Voltage : DC 36 V ; 2A
 - .Contact Resistance: 30 mohm maximum at Working Height(Quiescence)
- Mechanical
 - .Full store: 1.0 mm
 - .Working Store: 0.50 mm
 - .Spring Force : 40g±10g at Normal Working Height
 - .Durability:10,000 cycles(minimum)
- Environmental
 - .Operating Temperature: -40°C~+85°C
 - .Humidity Range: 10%RH~90%RH
 - .Salt Spray: 48 Hours
- When the current is greater than 1A then need to increase the time delay circuit(3 second)
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- To ensure the best usage,please operate it based on the working height.
- .RoHs&HF compliant product.

VER.	DESCRIPTION	ECN NO.	DATE

DRAWN	LX	DATE	2021.04.29			 Dongguan Promax Electronics Technology Co., Ltd	
CHECKED		SCALE	10:1	VER.	B.0		
APPROVED		TITLE	T33耳机天线弹针			Ang:	Dim:
PROJECT		DRAWING NO.	NC3196-01RA			0 ±1°	0 ±0.15
SHEET	1 of 1	UNIT	mm			.0 ±0.5°	.0 ±0.10
						.00 ±0.25°	.00 ±0.05