




Please Approve this Drawing

Date

Signature

NO.	Part Name	Q'TY	Material	Plated surface
1	Pin	6	Brass	Au 10u" Min. Over 50u" Min. Ni
2	Housing	1	High temp.Plastic; UL94 V-0	Color Black
3				
4				
5				



- NOTES:
- Electrical
 - .Rated Current & Voltage : DC 12 V ; 1.0A
 - .Contact Resistance:50 mohm maximum at Working Height(Quiescence)
 - .Insulation Resistance: 1000MΩ Min. at 1000VDC/Minute
 - .Dielectric Withstanding Voltage: At 500VAC/Minute No Breakdown
 - Environmental
 - .Operating Temperature: -40°C~+85°C
 - .Humidity Range: 10%RH~90%RH
 - .Salt Spray: 48 Hours
 - RoHs&HF compliant product.

DRAWN	lys	DATE	2021.05.28			 Dongguan Promax Electronics Technology Co., Ltd
CHECKED		SCALE	10:1	VER.	B.0	
APPROVED		TITLE	pin connector.			Ang:
PROJECT		DRAWING NO.	NF3341-06RA			0 ±1°
SHEET	1 of 1	UNIT	mm			.0 ±0.5°
						.00 ±0.25°
						Dim: 0 ±0.20
						.0 ±0.10
						.00 ±0.05

VER.	DESCRIPTION	ECN NO.	DATE