


Please Approve this Drawing	
Date	
Signature	

NO.	Part Name	Q'TY	Material	Plated surface
1	Plunger	2	C3604	AU 1 U" MIN OVER 50~100 U" NI
2	Barrel	1	C3604	AU 1 U" MIN OVER 50~100 U" NI
3	Spring	1	SUS304	Not Plated



NOTES:

- Electrical
 .Rated Current & Voltage : DC 12 V ; 1A
 .Contact Resistance:100 mohm maximum at Working Height(Quiescence)
- Mechanical
 .Spring Force : 70gf Min. at Normal Working Height
 .Durability: 10,000 cycles(minimum)
- Environmental
 .Operating Temperature: $-25^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 .Humidity Range: 10%RH~90%RH
 .Salt Spray: 48 Hours
- Part To Be Free Form Manufacturing Lubricants.
- When the current is greater than 1A then need to increase the time delay circuit(3 second)
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- To ensure the best usage,please operate it based on the working height.
- .RoHs&HF compliant product.

DRAWN	Roy	DATE	2017.07.31		 Dongguan Promax Electronics Technology Co., Ltd
CHECKED		SCALE	10:1	VER. B.0	
APPROVED		TITLE	pogo pin connector.		Ang:
PROJECT		DRAWING NO.	C756-01		0 $\pm 1^{\circ}$
SHEET	1 of 1	UNIT	mm		.0 $\pm 0.5^{\circ}$
					.00 $\pm 0.25^{\circ}$
					Dim: 0 ± 0.15
					.0 ± 0.10
					.00 ± 0.05

VER.	DESCRIPTION	ECN NO.	DATE