


Please Approve this Drawing	
Date	
Signature	

NO.	Part Name	Q'TY	Material	Plated surface
1	Plunger	1	brass	Au 5u" Min. OVER 50~120 U" CuZn
2	Barrel	1	brass	Au 5u" Min. OVER 50~120 U" CuZn
3	Spring	1	SUS	N/A
4				



NOTES:

- Electrical
 - .Rated Current & Voltage : DC 12 V ; 1.0A
 - .Contact Resistance: 100 mohm maximum at Working Height(Quiescence)
- Mechanical
 - .Full store: 3.60 mm
 - .Spring Force : 100gf±20%gf at Working Height
 - .Durability:10,000 cycles(minimum)
- Environmental
 - .Operating Temperature: -25°C~+85°C
 - .Humidity Range: 10%RH~90%RH
 - .Salt Spray: 48 Hours
- When the current is greater than 1A then need to increase the time delay circuit(3 second)
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- To ensure the best usage, please operate it based on the working height.
- .RoHs&HF compliant product.

DRAWN	LX	DATE	2022.09.02		 Dongguan Promax Electronics Technology Co., Ltd.
CHECKED		SCALE	10:1	VER. A.0	
APPROVED		TITLE	pogo pin		Ang:
PROJECT		DRAWING NO.	NC5127-01PA		0 ±1°
SHEET	1 of 1	UNIT	mm		.0 ±0.5°
					.00 ±0.25°
					Dim:
					0 ±0.15
					.0 ±0.10
					.00 ±0.05

VER.	DESCRIPTION	ECN NO.	1 of 1	DATE